



Product Name **ENGINE STOPLEAK**

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Supplier Name Dyna Fuels Australia
Address Factory 94 /38-40 Popes Road Keysborough 3173
Telephone (03) 97080023
Fax (03) 97080023
Emergency 0405749145
Web Site
Synonym(s) ES - PRODUCT CODE
Use(s) OIL ADDITIVE
SDS Date 19 Oct 2018

2. HAZARDS IDENTIFICATION

CLASSIFIED AS HAZARDOUS ACCORDING TO SAFE WORK AUSTRALIA CRITERIA

RISK PHRASES

R65 Harmful: May cause lung damage if swallowed.

SAFETY PHRASES

S2 Keep out of reach of children.
S23 Do not breathe gas/fumes/vapour/spray (where applicable).
S24 Avoid contact with skin.
S62 If swallowed, do not induce vomiting; seek medical advice immediately and show this container or label.

NOT CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE

UN No. None Allocated **DG Class** None Allocated **Subsidiary Risk(s)** None Allocated
Packing Group None Allocated **Hazchem Code** None Allocated

3. COMPOSITION/ INFORMATION ON INGREDIENTS

Ingredient	Formula	CAS No.	Content
SOLVENT NAPHTHA (PETROLEUM), HEAVY AROMATIC	Not Available	64742-94-5	30-60%
ADDITIVE(S)	Not Available	Not Available	<10%

4. FIRST AID MEASURES

Eye If in eyes, hold eyelids apart and flush continuously with running water. Continue flushing until advised to stop by a Poisons Information Centre, a doctor, or for at least 15 minutes.

Inhalation If inhaled, remove from contaminated area. To protect rescuer, use a Type A (Organic vapour) respirator or an Air-line respirator (in poorly ventilated areas). Apply artificial respiration if not breathing.

Skin If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water. Continue flushing with water until advised to stop by a Poisons Information Centre or a doctor.

Ingestion For advice, contact a Poison Information Centre on 13 11 26 (Australia Wide) or a doctor (at once). If swallowed, do not induce vomiting.



Product Name **ENGINE STOPLEAK**

Advice to Doctor Treat symptomatically.

5. FIRE FIGHTING MEASURES

Flammability	Combustible. May evolve toxic gases (carbon oxides, hydrocarbons) when heated to decomposition.
Fire and Explosion	Evacuate area and contact emergency services. Toxic gases may be evolved in a fire situation. Remain upwind and notify those downwind of hazard. Wear full protective equipment including Self Contained Breathing Apparatus (SCBA) when combating fire. Use waterfog to cool intact containers and nearby storage areas.
Extinguishing	Dry agent, carbon dioxide or foam. Prevent contamination of drains or waterways.
Hazchem Code	None Allocated

6. ACCIDENTAL RELEASE MEASURES

Spillage	Contact emergency services where appropriate. Use personal protective equipment. Clear area of all unprotected personnel. Ventilate area where possible. Contain spillage, then cover / absorb spill with non-combustible absorbant material (vermiculite, sand, or similar), collect and place in suitable containers for disposal. Eliminate all ignition sources.
-----------------	--

7. STORAGE AND HANDLING

Storage	Store in a cool, dry, well ventilated area, removed from oxidising agents, acids, heat or ignition sources and foodstuffs. Ensure containers are adequately labelled, protected from physical damage and sealed when not in use. Large storage areas should have appropriate ventilation systems. Store as a Class C1 Combustible Liquid (AS1940).
Handling	Before use carefully read the product label. Use of safe work practices are recommended to avoid eye or skin contact and inhalation. Observe good personal hygiene, including washing hands before eating. Prohibit eating, drinking and smoking in contaminated areas.

8. EXPOSURE CONTROLS/ PERSONAL PROTECTION

Exposure Stds	No exposure standard(s) allocated.
Biological Limits	No biological limit allocated.
Engineering Controls	Avoid inhalation. Use in well ventilated areas. Where an inhalation risk exists, mechanical extraction ventilation is recommended.
PPE	Wear splash-proof goggles, nitrile or viton (R) gloves and coveralls. Where an inhalation risk exists, wear: a Type A (Organic vapour) respirator. If spraying, wear: a Full-face Type A-Class P1 (Organic gases/vapours and Particulate) respirator.



9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	COLOURED LIQUID	Solubility (water)	INSOLUBLE
Odour	SLIGHT ODOUR	Specific Gravity	0.90 (Approximately)
pH	NOT AVAILABLE	% Volatiles	25 % (Approximately)
Vapour Pressure	< 0.1 kPa @ 20°C	Flammability	CLASS C1 COMBUSTIBLE
Vapour Density	NOT AVAILABLE	Flash Point	65°C (Approximately)
Boiling Point	> 150°C	Upper Explosion Limit	> 5 %
Melting Point	NOT AVAILABLE	Lower Explosion Limit	< 1 %
Evaporation Rate	NOT AVAILABLE		



Ultimate Engine Protection

Product Name **ENGINE STOPLEAK**

10. STABILITY AND REACTIVITY

Chemical Stability	Stable under recommended conditions of storage.
Conditions to Avoid	Avoid heat, sparks, open flames and other ignition sources.
Material to Avoid	Incompatible with oxidising agents (eg. hypochlorites), acids (eg. nitric acid), heat and ignition sources.
Hazardous Decomposition Products	May evolve toxic gases (carbon oxides, hydrocarbons) when heated to decomposition.
Hazardous Reactions	Polymerization is not expected to occur.

11. TOXICOLOGICAL INFORMATION

Health Hazard Summary	Moderate toxicity - irritant. This product has the potential to cause adverse health effects with over exposure. Use safe work practices to avoid eye or skin contact and inhalation. Chronic exposure to some solvents may result in central nervous system (CNS), liver and kidney damage.
Eye	Irritant. Contact may result in irritation, lacrimation, pain, redness and conjunctivitis. May result in burns with prolonged contact.
Inhalation	Irritant. Over exposure may result in irritation of the nose and throat, coughing, nausea, headache, fatigue, loss of appetite and vomiting. High level exposure may result in dizziness, breathing difficulties, pulmonary oedema and unconsciousness. Chronic exposure may result in kidney, liver and CNS damage.
Skin	Irritant. Contact may result in drying and defatting of the skin, rash and dermatitis. May be absorbed through skin with harmful effects.
Ingestion	Moderate toxicity. Ingestion may result in nausea, vomiting, abdominal pain, dizziness, fatigue and diarrhoea. Ingestion of large quantities may result in liver and kidney damage, and unconsciousness. Aspiration into lungs may cause chemical pneumonitis and pulmonary oedema.
Toxicity Data	SOLVENT NAPHTHA (PETROLEUM), HEAVY AROMATIC (64742-94-5) LC50 (Inhalation): > 590 mg/m ³ /4 hours (rat) LD50 (Skin): > 2 mL/kg (rabbit) LDLo (Ingestion): 5 mL/kg (rat)

12. ECOLOGICAL INFORMATION

Environment	If aromatic hydrocarbons are released to soil, they will evaporate from near-surface soil & leach to groundwater. Biodegradation occurs in soil & groundwater but may be slow, especially at high concentrations, which can be toxic to microorganisms. Will exist largely as vapour in air. Half life in atmosphere depends on particular hydrocarbon (eg 1-2 days (xylene); 3 hrs-1 day (toluene)).
--------------------	---

13. DISPOSAL CONSIDERATIONS

Waste Disposal	Wearing the protective equipment outlined, ensure all ignition sources are extinguished. For small quantities, absorb on paper, sand or similar and evaporate under a fume cupboard or open area. For large volumes, atomise into incinerator (mixing with more flammable solvent if required) or recycle by gravimetric separation, distilling & reusing. Contact the manufacturer for additional information if required.
Legislation	Dispose of in accordance with relevant local legislation.

14. TRANSPORT INFORMATION

NOT CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE

Shipping Name	None Allocated			
UN No.	None Allocated	DG Class	None Allocated	Subsidiary Risk(s) None Allocated
Packing Group	None Allocated	Hazchem Code	None Allocated	

15. REGULATORY INFORMATION

Poison Schedule	Classified as a Schedule 5 (S5) Poison using the criteria in the Standard for the Uniform Scheduling of Drugs and Poisons (SUSDP).
AICS	All chemicals listed on the Australian Inventory of Chemical Substances (AICS).

16. OTHER INFORMATION

Additional Information	RESPIRATORS: In general the use of respirators should be limited and engineering controls employed to avoid exposure. If respiratory equipment must be worn ensure correct respirator selection and training is undertaken.
-------------------------------	---



Ultimate Engine Protection

Product Name **ENGINE STOPLEAK**

Remember that some respirators may be extremely uncomfortable when used for long periods. The use of air powered or air supplied respirators should be considered where prolonged or repeated use is necessary.

WORK PRACTICES - SOLVENTS: Organic solvents may present both a health and flammability hazard. It is recommended that engineering controls should be adopted to reduce exposure where practicable (for example, if using indoors, ensure explosion proof extraction ventilation is available). Flammable or combustible liquids with explosive limits have the potential for ignition from static discharge. Refer to AS 1020 (The control of undesirable static electricity) and AS 1940 (The storage and handling of flammable and combustible liquids) for control procedures.

ABBREVIATIONS:

ACGIH - American Conference of Industrial Hygienists.
ADG - Australian Dangerous Goods.
BEI - Biological Exposure Indice(s).
CAS# - Chemical Abstract Service number - used to uniquely identify chemical compounds.
CNS - Central Nervous System.
EC No - European Community Number.
HSNO - Hazardous Substances and New Organisms.
IARC - International Agency for Research on Cancer.
mg/m3 - Milligrams per Cubic Metre.
NOS - Not Otherwise Specified.
pH - relates to hydrogen ion concentration using a scale of 0 (high acidic) to 14 (highly alkaline).
ppm - Parts Per Million.
RTECS - Registry of Toxic Effects of Chemical Substances.
STEL - Short Term Exposure Limit.
SWA - Safe Work Australia.
TWA - Time Weighted Average.

HEALTH EFFECTS FROM EXPOSURE:

It should be noted that the effects from exposure to this product will depend on several factors including: frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare a Chem Alert report which would encompass all possible scenarios, it is anticipated that users will assess the risks and apply control methods where appropriate.

PERSONAL PROTECTIVE EQUIPMENT GUIDELINES:

The recommendation for protective equipment contained within this Chem Alert report is provided as a guide only. Factors such as method of application, working environment, quantity used, product concentration and the availability of engineering controls should be considered before final selection of personal protective equipment is made.

Report Status This document has been compiled by RMT on behalf of the manufacturer of the product and serves as the manufacturer's Safety Data Sheet ('SDS').

It is based on information concerning the product which has been provided to RMT by the manufacturer or obtained from third party sources and is believed to represent the current state of knowledge as to the appropriate safety and handling precautions for the product at the time of issue. Further clarification regarding any aspect of the product should be obtained directly from the manufacturer.

While RMT has taken all due care to include accurate and up-to-date information in this SDS, it does not provide any warranty as to accuracy or completeness. As far as lawfully possible, RMT accepts no liability for any loss, injury or damage (including consequential loss) which may be suffered or incurred by any person as a consequence of their reliance on the information contained in this SDS.

SDS Date 19 Oct 2018

End of Report